

aiwa

TV WALL BRACKET

AE-K70

Important Safety Instructions

1. This product comes with small parts that could cause suffocation if swallowed. Keep away from children.
2. To avoid the risk of property damage, do not begin installation until you have finished reading this manual and understand how to install the wall bracket. If you don't understand any of the steps, please contact a qualified installer.
3. Make sure the wall bracket can be attached to your TV before drilling holes on your wall.
4. Do not use for TVs weighing more than 55kg.
5. The wall to which this wall bracket is attached must be able to support the combined load of the wall bracket and the TV. The wall bracket's weight limit assumes that the supporting wall is appropriate to hold a 55kg load.
6. Check the wall bracket attachment every couple of months to make sure it is still securely attached.
7. This wall bracket must be installed on a wall with timber studs, or a solid concrete or brick wall. If installed on a timber stud wall, make sure the mounting screws are anchored into the centre of the studs. If installed on a concrete or brick wall, make sure the mounting screws are installed in the solid section of the concrete/brick. For other wall types, different screws may be required. If necessary, please contact a qualified installer.
8. This product is for indoor use only.

Technical Specifications:

Maximum load capacity: 55kg

Compatible TV sizes: 40" – 75"

VESA compatibility: 200×200, 300×300, 400×400 and 600x400 mm

Maximum wall mounting dimensions: 640mm x 155mm

Tilt degree: -15 degree to +15 degree

Distance from wall: 45mm

Tools Required:

Pencil

Electric Drill

Screwdriver












Stud Finder

Spirit Level (included)



aiwa

Instruction Manual

A		M5x16 (TV Screw)	4	F		Handle screw	2
B		M6x16 (TV Screw)	4	G		M6x50 (Wall Screw)	4
C		M8x20 (TV Screw)	4	H		Concrete Anchor	4
D		M5x35 (Safety Screw)	2	I		Gasket	4
E		Tilt Adjustment Handle	2	J		M6-4 / M8-4 (Washer)	
				K		Spirit Level	1

Overview.

